

(b) When pipelines are protected by rectifiers or anodes for which the initial life expectancy of the cathodic protection system either cannot be calculated or calculations indicate a life expectancy of less than 20 years, such pipelines shall be inspected annually by taking measurements of pipe-to-electrolyte potential measurements.

§ 250.1006 Abandonment and out-of-service requirements for DOI pipelines.

(a)(1) A pipeline may be abandoned in place if, in the opinion of the Regional Supervisor, it does not constitute a hazard to navigation, commercial fishing operations, or unduly interfere with other uses in the OCS. Pipelines to be abandoned in place shall be flushed, filled with seawater, cut, and plugged with the ends buried at least 3 feet.

(2) Pipelines abandoned by removal shall be pigged, unless the Regional Supervisor determines that such procedure is not practical, and flushed with water prior to removal.

(b)(1) Pipelines taken out-of-service shall be blind flanged or isolated with a closed block valve at each end.

(2) Pipelines taken out-of-service for a period of more than 1 year shall be flushed and filled with inhibited seawater.

(3) Pipelines taken out-of-service shall be returned to service within 5 years or be abandoned in accordance with the requirements of paragraph (a) (1) or (2) of this section.

§ 250.1007 What to include in applications.

(a) Applications to install a lease term pipeline or for a pipeline right-of-way grant must be submitted in quadruplicate to the Regional Supervisor. Right-of-way grant applications must include an identification of the operator of the pipeline. Each application must include the following:

(1) Plat(s) drawn to a scale specified by the Regional Supervisor showing major features and other pertinent data including area, lease, and block designations; water depths; route; length in Federal waters; width of right-of-way, if applicable; connecting facilities; size; product(s) to be trans-

ported with anticipated gravity or density; burial depth; direction of flow; X-Y coordinates of key points; and the location of other pipelines that will be connected to or crossed by the proposed pipeline(s). The initial and terminal points of the pipeline and any continuation into State jurisdiction shall be accurately located even if the pipeline is to have an onshore terminal point. A plat(s) submitted for a pipeline right-of-way shall bear a signed certificate upon its face by the engineer who made the map that certifies that the right-of-way is accurately represented upon the map and that the design characteristics of the associated pipeline are in accordance with applicable regulations.

(2) A schematic drawing showing the size, weight, grade, wall thickness, and type of line pipe and risers; pressure-regulating devices (including back-pressure regulators); sensing devices with associated pressure-control lines; PSV's and settings; SDV's, FSV's, and block valves; and manifolds. This schematic drawing shall also show input source(s), e.g., wells, pumps, compressors, and vessels; maximum input pressure(s); the rated working pressure, as specified by ANSI or API, of all valves, flanges, and fittings; the initial receiving equipment and its rated working pressure; and associated safety equipment and pig launchers and receivers. The schematic must indicate the point on the OCS at which operating responsibility transfers between a producing operator and a transporting operator.

(3) General information as follows:

(i) Description of cathodic protection system. If pipeline anodes are to be used, specify the type, size, weight, number, spacing, and anticipated life;

(ii) Description of external pipeline coating system;

(iii) Description of internal protective measures;

(iv) Specific gravity of the empty pipe;

(v) MSP;

(vi) MAOP and calculations used in its determination;

(vii) Hydrostatic test pressure, medium, and period of time that the line will be tested;

(viii) MAOP of the receiving pipeline or facility,